

27.5*12.0*9.8

-40 to +85

1.5kV

100%

3

I A 1 - 05 D 05

1 2 3 4 5

1. I A 1500V DC/DC
2. 1
3. 05
4. D Dual ()
5. 05 ± 5V +5V Vo1

(

DC-DC
1WI A1-XXDY


IA1-24D05	24 (22. 8- 25. 2)	± 5	± 100	± 10	1200	68
IA1-24D12		± 12	± 42	± 4	220	64
IA1-24D15		± 15	± 33	± 3	220	62
IA1-24D24		± 24	± 21	± 2	100	63

	/	5VDC	—	286/8	304/-	mA
		12VDC	—	115/8	121/-	
		24VDC	—	60/8	66/-	
		—	15	—		

— — ± 3 %

DC-DC
1WI A1-XXDY

			10-150Hz 5G 0.75mm along X Y and Z			
		MIL-HDBK-217F@25	3500	—	—	k hours
		UL94V-0				
		27.5*12.0*9.8mm				
		4.9g				
EMC	EMI		CI SPR32/EN55032 CLASS B			
			CI SPR32/EN55032 CLASS B			
	EMS		IEC/EN61000-4-2 Contact± 6kV/Air± 8kV perf. Criteria B			



mm [inch]

± 0.5mm

