

800W SMC800



(90-264VAC)

200*121*50mm

/ / / /

		± 2.0%			
		± 0.5%			
		± 1.5%			
	()	3000ms	50ms/230VAC		
	()	10ms/230VAC			
		90-264VAC			
		100-240VAC			
		47-63Hz			
	()	PF 0.95/230VAC			
	()	12A/115VAC 6A/230VAC			
	()	40A/230VAC			
	()	5mA/240VAC			
		110-140%			
			24V	36V	48V
			27-32V	40-48V	55-60V
		-30 to +70 (" ")			
		20-90%RH			
		-40 to +85 10-95%RH			
		0.03%/(0 -50)			
		10-500Hz 5G 10 / X Y Z 60			
3		GB4943.1-2011			
		I/P-O/P 2kVAC I/P-FG(CASE) 1.5kVAC O/P-FG(CASE) 0.5kVAC			
		I/P-O/P I/P-FG O/P-FG 100MChms/500VDC 25 70% RH			
		EN55011 EN55032 (Cl SPR32) CLASS B			
		IEC/EN 61000-4-2 Level 4 Contact 4kV/Air 8kV			
		IEC/EN 61000-4-3 Level 3			
		IEC/EN 61000-4-4 Level 3			
		IEC/EN 61000-4-5 Level 3 L-N 1kV L/N-FG 2kV			



sales@oeygo.net



+86(20) 3214 4470



51 E